

Purdue University
School of Aeronautics, Astronautics, and Engineering Sciences
Lafayette, Indiana

TOWED VEHICLE SYSTEMS

N 6 6 . 3 . 9 . 4 0 . 7 .

FACILITY FORM 602

(ACCESS OR NUMBER)
31
(ISSUE)
CP-78754
(NASA OR ORTHOGRAPHIC NUMBER)

(THRU)
1
(CODE)
23
(CATEGORY)

by

Joseph Genin

GPO PRICE \$ _____

CFSTI PRICE(S) \$ _____

Hard copy (HC) 2.00

Microfiche (MF) .50

653 July 65

July 1966

This research was supported under
NASA Grant NGR 15-005-021
to the Space Mechanics Area.

AA&ES 66-7

TOWED VEHICLE SYSTEMS

by

Joseph Genin*

July 1966

This research was supported under NASA Grant NGR 15-005-021 to the Space Mechanics Area.

*Associate Professor of Aeronautics, Astronautics, and Engineering Sciences
Purdue University

ACKNOWLEDGMENT

The writer wishes to thank Dr. S. J. Citron for helpful discussions during the course of the work contained herein and Mr. T. C. Cannon for his help in preparing Section V of this report. This research was supported under NASA Grant NGR 15-005-021 to the Space Mechanics Area.

SUMMARY

This report is divided into three parts. The first part (Sections I through IV) is a summary of the results of a literature survey conducted on the general topic of towed vehicle systems. The second part (Section V) is an analytical development which demonstrates that one of the fundamental assumptions which most investigators have made (considering the tow cable's tangential frictional force to be negligible) is incorrect. The third part (Section VI) is a bibliography.

I. INTRODUCTION

Since the problem areas encountered are quite similar the survey covers both airborne and submersible systems. Briefly, the conclusion of the survey is that much work remains to be done (both theoretically and experimentally) before a significantly greater level of understanding than currently exists is achieved in the area of towed vehicles.

No attempt is made herein to indicate the many and varied areas of applicability for the solution of the towed vehicle problem; especially since many applications in this era of heavy government support of research are classified. Rather, a general description of the technical problem areas is presented. Also, in an effort to enable the reader to follow the evolutionary path of the many investigators brief abstracts are given for some of the references in the bibliography, Section VI. The bibliography is by no means an attempt to list all of the numerous references found, for they are extensive in number and in the large most have not contributed significantly to furthering the state of the art. Rather it represents a sampling from which the interested reader can, hopefully, obtain an appreciation of the magnitude and scope of the problem area.

One of the odd features of this topic area is that relatively few of the research reports written on towed vehicles have been published in journals. This feature has resulted in vast duplication of effort; especially in the last five years during which time agencies of several governments have been supporting research efforts in the area of the stability of towed vehicles.

II. GLAUERT'S MATHEMATICAL MODEL

Most researchers tend to duplicate (both by intent and inadvertently) the works of Glauert [1, 2] who published his papers on the stability of an

airborne non-lifting towed vehicle in rectilinear motion in 1930 and 1934 respectively.

Glauert's analyses incorporate flexible cables and make the assumption of straight, level flight in which the cable moves from one equilibrium shape to the next (an instantaneous displacement) while the towed vehicle behaves dynamically. Another assumption made by Glauert, which like the above, later investigators have also adopted is that the cable drag is perpendicular to the cable. That is, there exists no skin friction component. This greatly simplifies the equations which determine the shape of the cable. However, quoting from Glauert, "Further investigation is necessary to examine the dynamical effects on the wire (cable) which are ignored in the present analysis."

Glauert's investigations were directed towards developing stability criteria for both longitudinal and lateral perturbations for an assumed equilibrium position for non-lifting bodies. His results are presented parametrically; the parameters being combinations of cable length, cable weight, towed body weight, ratio of drag of cable to drag of towed body, and angle of inclination of cable. He did not attempt to couple the longitudinal and lateral stability problems.

Of the many investigations which followed Glauert's work the most significant contribution was made in 1947 by L. Landweber and M. H. Protter [3]. It is equally significant that this paper has gone completely unnoticed by subsequent researchers and as a consequence none of the investigations conducted since yield results delicate enough to be termed better than "adequate." The main contribution of [3] is that the authors included the tangential friction force of the towing cable in their mathematical model and, using measured quantities for this force, demonstrated that the equilibrium configuration of the system is altered appreciably by the tangential drag. Some completely independent

studies have been made in recent years on this problem, but they fail to achieve the elegance of [3] and consequently never demonstrate the importance of the tangential drag. Landweber and Protter did not glean all of the useful information which can be obtained from a slight modification of their mathematical model. Specifically, they failed to formulate a moment equation which is non-trivial. In Glauert's case the moment equation is trivial because his mathematical model reduces to a system of concurrent forces. The results of [3] are presented in what might be termed a complicated form because the authors resorted to numerical means to solve the resulting equations. In Section V we, with computer solution in mind, derive the basic equations and present them in a very simple form. We also develop the moment equation referred to above. Equally important is that the illustrative examples given in [3] are for water whereas the results of our study are illustrated for air.

III. SOME OTHER TYPES OF INVESTIGATIONS

An unfortunate waste was created by the excessive duplication of effort by the many investigators. The mathematical models which they used are very much similar to Glauert's; which is quite understandable sans the benefit of the experience of the others (especially Landweber and Protter). This has resulted in models which are necessarily crude (Glauert emphasizes this) to facilitate the mathematics. Accordingly, the results are at best of a first order approximation. However, the model(s) have proven to be adequate for determining some of the fundamental problem areas; a fact which is borne out by experimental work. For example Shanks [5, 6, 7, 8] has done a considerable amount of research on the lateral stability of towed, lifting airborne vehicles. Shanks' efforts differ from most other investigations in that he seeks ways of stabilizing an unpiloted towed vehicle (a difficult analytical undertaking)

rather than accepting a given configuration and determining (parametrically) regions of unpiloted stability for it.

Perhaps the most unusual (and most pessimistic) paper written concerning the stability of towed vehicles is that of Söhne [9] , who was a glider pilot in World War II. His theoretical study was his dissertation (1947).

"... blind towed flight of long duration is impossible. If the towing airplane is lost sight of, the pilot of the towed airplane is forced usually after a few seconds to release the towline." One must keep in mind that this paper was written prior to the "electronics age."

As indicated above a number of investigations have been conducted with the towing environment being water. See references 10 through 12 and 15 through 26. However, many of these studies have placed primary emphasis on the towed vehicle (hydrofoils, instrument packages, etc.); the system analysis being of passing interest to the investigators. Even those reports which are concerned with the system prove to be less searching studies than some of the studies conducted with airborne vehicles, although once more [3] is an exception to this criticism. The latter criticism stems mainly from the investigators reluctance to make any concession for the difference in media from Glauert's work. For example [10] is virtually a duplication of a small part of Glauert's work. Nevertheless, despite their many shortcomings the authors of [11, 12] made the only reasonable attempt uncovered in this survey to analyze a towed vehicle in a turn. They do this considering fully submerged hydrofoils, for which they establish stability criteria. It is of interest to note that no experimental projects were initiated to verify their findings.

IV. BASIC PROBLEM

The basic system of concern in the study of the towed vehicle problem

consists simply of a towing vehicle, a cable and the towed vehicle, which can be lifting or non-lifting.

Focusing on one of the several logical starting points in the analysis of the airborne system, the cable connection to the towing vehicle, the complexity of the general problem becomes evident. All the reports studied begin with the assumption that the dynamic properties of the towing vehicle are completely known and that its flight pattern is stable. Any other assumption, such as the towing craft moving through a region of turbulence is, in effect, to place a forcing function on the cable. This, of course, would create traveling waves in the cable making the analysis of the system (the cable dynamics superimposed upon the dynamics of the towed vehicle) quite complex. It is obvious, of course, that the forcing function can also originate at the connection of the towed vehicle to the cable. It has been argued [13] that for low velocities (approximately 200 mph at sea level) that the traveling wave damps out and can be neglected. The entire problem of high subsonic velocities and supersonic velocities has not been investigated analytically. The transition velocity range would no doubt prove to be an interesting study.

Reference [14] carries Glauert's work one significant step further by showing that there exists a critical (unstable) speed range. It is interesting to note that the authors of [14] were very apologetic, stating that they were not aware of and thus for the most part duplicated Glauert's work.

Reference [13] aside from being a fair review of the state of the art, sans [3], contains as its main contribution parametric studies of the longitudinal and lateral stability of lifting bodies both coupled and uncoupled. This is accomplished by studying the equations of motion (using linear theory) on an analog computer.

The literature does not contain any reference to the study of towed

elastic bodies. The aeroelastic analysis of lifting bodies in free flight remains a complex problem to analyze. An extreme but relatively simple case, the structural stability of a right circular cylindrical shell (missile) with arbitrary boundary conditions under the action of a longitudinal pulsating load, is receiving considerable attention in the literature. Thus, it is seen that this small, significant portion of the overall system is not easily attacked or solved.

Nevertheless, the ultimate problem to pursue is the stability of a three dimensional, multi-degree of freedom, damped, elastic, towed vehicle, both lifting and non-lifting, considering both rectilinear motion and turns. The state of the art is such that we are a long way off from being able to make a meaningful analytical analysis of this problem. The fundamental mathematical model must be improved incrementally, supported by a parallel experimental effort.

V. EQUILIBRIUM CONFIGURATION AND TENSION OF A LIGHT FLEXIBLE CABLE IN A UNIFORM FLOW FIELD.

In this section we present the results of our study of the effect of a cable's tangential drag force on the orientation of a tow vehicle system, demonstrating that the skin friction force is not a negligible effect as most investigators, sans proof, have assumed. The equations developed should prove to be a valuable starting point in future investigations to determine stability criteria for the system, and equally important they can be used by practicing engineers to obtain more accurate estimates of cable shapes.

Two fundamental categories into which tow vehicle studies may be divided are light (negligible weight) and heavy cables. In that our purpose was to display the effect of skin friction and in that in most cases the weight of the cable is negligible in comparison to that of the body being towed we confined the study to the case of the light cable. More important, this assumption aided in simplifying the resulting equations so that attention was properly

focused on the effect of skin friction. The other assumptions made were steady-state aerodynamics, constant tow vehicle velocity, equilibrium configuration for the tow cable (hence system), and the airplane and towed vehicle were assumed to be rigid bodies. The last assumption allowed for constant values of lift and drag to be employed for the towed vehicle when in straight flight at a constant speed. These assumptions are discussed at length in many of the reports listed in the bibliography and will not be repeated herein.

Figure 1 is a sketch of the system analyzed, defining a few of the variables which appear in the development below.




Figure 1 - TOW VEHICLE SYSTEM

A free body diagram of a generic segment of the cable of length ds is shown in Figure 2.




Figure 2 - FREE BODY DIAGRAM

Summing forces in directions tangent and normal to the cable at point A we obtain after making a small angle assumption on $d\varphi$

$$dZ = dT \quad (1)$$

and

$$T d\varphi - dN = 0 \quad (2)$$

Let us write the tangential drag per unit length as

$$dZ = f(\varphi) ds \quad (3)$$

and the normal component per unit length as

$$(4)$$

$$dN = g(\varphi) ds$$

where $f(\varphi)$ and $g(\varphi)$ are experimentally determined and are functions of the velocity of the cable. It turns out that $g(\varphi)$ can be expressed as

$$g(\varphi) = K \cos^2 \varphi$$

where K , of course is a function of the velocity of the cable. Thus Eqn.

(4) may be rewritten as

$$dN = K \cos^2 \varphi ds \quad (5)$$

It facilitates computations to leave (3) in its present form for now.

We will now formulate the governing differential equation for the determination of cable shapes. Placing (5) into (2) we obtain

$$T d\varphi - K \cos^2 \varphi ds = 0 \quad (6)$$

T may be determined by placing (3) into (1) and integrating. Thus,

$$T = \int f(\varphi) ds + c \quad (7)$$

Hence, from (6) and (7) we obtain

$$\left(\int f(\varphi) ds + c \right) d\varphi - K \cos^2 \varphi ds = 0 \quad (8)$$

Dividing (8) by $d\varphi$ yields

$$\int f(\varphi) ds + c - K \cos^2 \varphi \frac{ds}{d\varphi} = 0 \quad (9)$$

Taking $\frac{d}{ds}$ of (9)

$$f(\varphi) - \frac{d}{ds} \left(K \cos^2 \varphi \frac{ds}{d\varphi} \right) =$$

$$f(\varphi) + 2K \cos \varphi \sin \varphi - K \cos^2 \varphi \frac{d\varphi}{ds} \frac{d^2 s}{d\varphi^2} = 0$$

or

$$\frac{d^2 s}{d\varphi^2} - q(\varphi) \frac{ds}{d\varphi} = 0, \quad (10)$$

where

$$q(\varphi) = \frac{f(\varphi) + 2K \cos \varphi \sin \varphi}{K \cos^2 \varphi} \quad (11)$$

Using Eqn. (10) and the geometric relations

$$dx = \sin \varphi ds \quad (12)$$

and

$$dy = \cos \varphi ds \quad (13)$$

it is easy to make comparative studies between Glauert's model which neglects the effects of skin friction and our mathematical model which, of course, includes the effects of skin friction. However, before doing that let us develop one more valuable equation by selecting a slightly altered mathematical model; that

is, another free body diagram.

Let O be the center of gravity of the towed body which was assumed to be a particle. Hence the center of gravity is the geometric center and lies on the cable. Thus, we have the free body diagram shown in Figure 3.




Figure 3. - MODEL FOR MOMENT CALCULATION

In Figure 3 \bar{r} represents the position vector measured from O to any point on the cable. Thus,

$$\bar{r} = x \bar{i} + y \bar{j} \quad (14)$$

The cable force \bar{T} may be written as

$$\bar{T} = T(\sin \phi \bar{i} + \cos \phi \bar{j}) \quad (15)$$

Similarly we may form

$$d\bar{r} = dr(-\sin \phi \bar{i} - \cos \phi \bar{j}) \quad (16)$$

and

$$d\bar{N} = dN(-\cos \phi \bar{i} + \sin \phi \bar{j}) \quad (17)$$

Taking moments about point O we have

$$\sum M_o = 0 = \bar{r} \times \bar{T} + \int_0^s \bar{r} \times (d\bar{r} + d\bar{N}) \quad (18)$$

Placing Eqns. (14) through (17) into (18) we obtain

$$T(X \cos \varphi - Y \sin \varphi) + \int_0^s \left\{ \frac{dZ}{ds} (-x \cos \varphi + y \sin \varphi) + \frac{dN}{ds} (x \sin \varphi + y \cos \varphi) \right\} ds = 0$$

where X and Y are as defined in Figure 3 (say the point of contact with the towing vehicle). We can now replace T , dN and dZ in the last equation by using Eqns. (2), (3) and (5). The result is

$$K \cos^2 \varphi \frac{ds}{d\varphi} (X \cos \varphi - Y \sin \varphi) + \int_0^s \left\{ f(\varphi) (-x \cos \varphi + y \sin \varphi) + K \cos^2 \varphi (x \sin \varphi + y \cos \varphi) \right\} ds = 0 \quad (19)$$

Eqn. (19) allows for the complete determination of a cable configuration for a given physical problem. The potency of the equation is self evident. In our next report we will develop a more general equation taking the cable weight into account. Therefore, we will not dwell on the moment formulation herein.

Let us now return to Eqns. (10) through (13). Define $\gamma' = K/T_0$ where T_0 is the tension in the cable at $\varphi \equiv 0$. Thus, nondimensionalizing the lengths s , x and y we obtain

$$\left. \begin{aligned} \sigma &= s \gamma' \\ \xi &= x \gamma' \\ \eta &= y \gamma' \end{aligned} \right\} \quad (20)$$

Placing (20) into (10) we obtain

$$\frac{d^2 \sigma}{d\varphi^2} - g(\varphi) \frac{d\sigma}{d\varphi} = 0 \quad (21)$$

The boundary condition necessary to integrate Eqn. (21) is obtained from Eqn. (6). We have defined

$$T_0 = T|_{\varphi=0}$$

Therefore from (6) in nondimensional form we have

$$\left. \frac{dr}{d\varphi} \right|_{\varphi=0} = 1$$

as the boundary condition. Using this boundary condition Eqn. (21) was integrated by computer using a Runge Kutta scheme and the resulting curves for cable shapes were plotted.

Intuitively one would expect the tangential drag to increase with velocity and tend to force the cable to approach a straight line configuration in the limit. Hence to illustrate the importance of the frictional force we have selected an extremely low velocity for our illustrative example. To this end experimental data was taken from [4] which was measured in a flow of 40 ft./sec. Thus by a curve fitting process $f(\varphi)$ was computed to be

$$f(\varphi) = 0.0134 \left(\frac{\varphi}{\pi} \right) + 0.0072 \left(\frac{\varphi}{\pi} \right)^2 - 0.0504 \left(\frac{\varphi}{\pi} \right)^3$$

Figure 4 contains comparative curves for the case where the drag of the towed vehicle is negligible. Thus it is solely a theoretical result. The zero towed body drag produces a vertical tangent at the point of contact of towed vehicle and cable.


Figure 5 contains comparative curves for an arbitrary set of input data of drag and lift for the towed body which results in an angle φ at the cable-towed vehicle connection of 0.6 radians.

The significant difference in the curves of Figures 4 and 5 is entirely

due to the effect of tangential drag. Physically, when one eliminates this effect he, in essence, is making the assumption that the tension throughout the cable is constant. Thus, there is but one possible cable configuration for the Glauert case. It is a fair first approximation and mathematically Glauert's equations are easier to work with than the equations developed above but as the study shows the Glauert results are not sufficiently delicate for accurate work.

FIGURE 4


EFFECT OF CABLE SKIN FRICTION WHEN TOWED BODY HAS NEGLIGIBLE DRAG.



Note: C equals the length of cable whose normal drag is equal to the tension [Glauert's case].

FIGURE 5

COMPARATIVE STUDY FOR A TOWED LIFTING BODY



Note: C equals the length of cable
whose normal drag is equal to the tension
[Glaueert's case].

VI. BIBLIOGRAPHY

1. The Stability of a Body Towed by a Light Wire, Glauert, H., Aeronautical Research Committee, R & M 1312, 1930.

The stability of a body towed by a light inextensible wire has been investigated on certain simplifying assumptions regarding the force experienced by the wire. In addition to the pitching and yawing oscillations of the body there are three oscillations of the whole system. The most important oscillation is associated with a bowing of the wire in the plane of symmetry, and, even if the body has satisfactory statical stability, this oscillation may become unstable if the body is too short or if the drag of the body is low compared with that of the wire.

2. The Form of a Heavy Flexible Cable Used for Towing a Heavy Body Below an Aeroplane, Glauert, H., ARC, R & M 1592, 1934.

The mathematical expressions for the form of a heavy cable in a wind have been known for many years, but no systematic numerical results are available. Calculations have been made to derive a family of curves, depending on the weight-drag ratio of the cable, which should suffice to cover all practical problems, involving the towing of a heavy body. The use of the curves is illustrated by a typical numerical example.

3. The Shape and Tension of a Light Flexible Cable in a Uniform Current, Landweber, L., and Protter, N. H., ASME Journal of Applied Mechanics, Vol. 14, No. 2, June 1947, pp. A-121-A-126.

The authors consider the several cases of a towing cable in which the frictional forces as well as the normal forces are taken into account in

determining the shape of the cable, the weight of the cable being neglected. Equations and curves are derived by means of which any problem of this type, involving towing cables or loops, can be treated. Examples are given which illustrate solutions to various towline problems.

4. Tests on Smooth and Stranded Wires Inclined to the Wind Direction, and a Comparison of Results on Stranded Wires in Air and Water, Relf, E. F., and Powell, C. H., Aeronautical Research Committee R&M No. 307, January 1917.
5. Experimental Investigation of the Dynamic Stability of a Towed Parawing Glider Model, Shanks, R. E., NACA TND-1614, March, 1963.
6. Experimental Determination of the Lateral Stability of a Glider Towed by a Single Towline and Correlation with an Approximate Theory, Maggin, B., and Shanks, R. E., NACA RM No. L8H23, Nov., 1948.

The approximate theory developed herein for lateral stability is quoted frequently.
7. Experimental Investigation of the Dynamic Stability of a Towed Parawing Glider Air Cargo Delivery System, Shanks, R. E. NASA TN D-2292, August, 1964.
8. Investigation of the Dynamic Stability and Controllability of a Towed Model of a Modified Half-Cone Reentry Vehicle, Shanks, R. E., NASA TN D-2517, February, 1965.
9. Directional Stability of Towed Airplanes, Sohne, W., NACA, T. M. 1401.
10. The Steady, Rectilinear Towing of a Weightless Hydrofoil-Cable System in a Non-Uniform Stream, Pepper, P.A., and Streich, J., ONR Contract No. NONr-3582 (oo), EDO Corporation Report 5709, January, 1962.
11. The Equilibrium Configuration of a Towed Hydrofoil-Strut System in Two-Dimensional Steady Turns, Pepper, P.A., and Streich, J., ONR Contact No.

NONr-3852 (oo), EDO Corporation Report 5741, April 1962.

12. The Equilibrium Configuration of a Towed Hydrofoil-Cable System in Two-Dimensional Steady Turns, Pepper, P.A., ONR Contract No. NONr-3582 (oo), EDO Corporation Report 5822, January, 1964.
13. On the Stability of Airborne Towed Vehicles, Burton, M., and Parsmore, H., Princeton University, May, 1962, 1 vol.

Studies of the dynamic stability of heavy bodies with lifting surfaces towed behind an airplane. Following a fairly complete analysis of cable dynamics, analyses of the longitudinal, lateral and coupled motions of the system are developed and discussed. A current configuration is chosen as starting point from which the studies are expanded to develop stability boundaries of the important parameters.

14. Aerodynamic Instability of Non-Lifting Bodies Towed Beneath an Aircraft, Etkin, B., and MacKworth, J. C., Institute of Aerophysics, University of Toronto, UTIA Technical Note No. 65, January, 1963.

A theoretical and experimental (wind tunnel) investigation was made of the stability of a heavy body towed on a light cable beneath an aircraft. The theory showed the possible existence of a band of speeds within which the body is dynamically unstable, (swinging sideways). The experiments confirmed this prediction, and showed good agreement with the calculated values of the two critical speeds which bound the unstable region. The calculated and measured periods of oscillation also were in good agreement.

15. The Configuration of a Cable Towing a Heavy Submerged Body from a Surface Vessel, ASTIA, AD No. 333952.
16. Preliminary Design of a Cable-Towed Oceanographic Instrumentation System, Ellsworth, W., and Gay, S., Pneumodynamics Corp., February, 1961, 94 pp.
17. Design Study and Experimental Program for a Helicopter-Towed Sonar System,

G. D./Convair, Final Report, April, 1964, 145 pp.

18. Predicted Hydrodynamic Characteristics of the AN/SQA-10 Variable Depth Sonar Vehicle, Spanger, P., David Taylor Model Basin, February, 1965, 15 pp.
Based on scale model tests, the steady towing behavior and some hydrodynamic characteristics of a full-scale AN/SQA-10 variable depth sonar vehicle are predicted for various speeds. These characteristics include trim-tab effectiveness and cable tension and angle at the vehicle. The predicted behavior for the condition investigated indicates that the vehicle will satisfy Bureau of Ships specifications.
19. Heaving Forces and Pitching Moments on a Semi-submerged and Restrained Prolate Spheroid Proceeding in Regular Head Waves, Lee, C., Institute of Engineering Research, January, 1964, 79 pp.
Describes experiments in which heaving forces and pitching moments were measured on a semi-submerged spheroid which was towed at a constant speed in regular head waves.
20. Factors Effecting the Design of a System for Towing a Body on a Long Length of Wire, Stevens, G., Royal Aircraft Establishment (G. Brit.), March, 1961, rev. September, 1962, 21 pp.
A method of calculating the diameter of wire to be used and the drag area of target to be towed in order to meet a given requirement of maximum speed of towing and maximum length of tow is presented. Particular reference is made to a towed target system of the Del Mar Company of Los Angeles and further analysis is made of U. S. Air Force test data on this system. Analysis predicts that there is a region at high subsonic airspeed and at medium altitudes where the towed system can become unstable.
21. Stability and Drag of Towed Underwater Bodies, Admiralty Underwater Weapons Establishment (G. Brit.), 1963.

22. Effects of Certain Ship Motions on Cable Tension in Systems for Handling Submerged Bodies, Rakoff, F., Navy Underwater Sound Lab., 7 August 1962, 27 pp.

Certain conclusions are reached concerning the characteristics of towed bodies, especially ship-towed fish or sonar systems, with respect to weight and mass.

23. The Transmission of Vibration by Towed Cables, Lyon, R., Bolt, Beranek, and Newman, Inc., 28 May 1962, 36 pp.

Cables of the order of a few cm. in diameter, moving in water and having an average density of 1 to 8 gm/c.c. are considered. The speed of motion will be taken in the range of 50-500 cm/sec. For a kinematic viscosity of $1/100 \text{ cm}^2/\text{sec}$. appropriate for water, the diameter Reynolds number is in the range 10,000 to 100,000. Vortex shredding may be expected to be the principal source of vibration transmission.

24. Note on the Stability of Tubular Elastic Bodies Towed in Water, Coad, S., and Hollings, D., Admiralty Underwater Weapon Establishment (G. Brit.), July, 1962, 9 pp.

25. Vibration and Towing Characteristics of Surface-Suspended Hydrophone Systems, Walton, C., and Merriam, M., David Taylor Model Basin.

An experimental investigation to determinate sources and methods of reducing cable vibrations in acoustic measuring systems, to provide information concerning full-scale towing behavior, and to accurately define the towing configuration of such systems.

26. A Synthesis and Discussion of Towing Arrangements for Large, Variable Depth Sonar Systems Internal to a Ship, Fridge, H., Navy Underwater Sound Lab., 6 February 1962, 11 pp.

27. Forces Measured in a Towline During Towing Tests of a Series G-60 High-

Speed Sled Target, McGinley, J. C., DTMB Report 589, 1947.

28. Wind Tunnel Test of Three Towed Winged Vehicles, Loezos, S., David Taylor Model Basin, January, 1964, 31 pp.

Static stability characteristics of 3 prototype towed vehicles: the Gruman ASQ-46, Johnsonville HTM-109, and Johnsonville HTM-110, were obtained by subsonic wind tunnel tests.

29. The Hydrodynamic Design of a Cable-Towed Body Suitable for Economical Productions, Gay, S., David Taylor Model Basin, December, 1959, 23 pp.

The general hydrodynamic requirements are listed and the design approach is described. Basin tests of a prototype body indicate that the design requirements were satisfactorily achieved.

30. General Design Criteria for Cable-Towed Body Systems Using Faired and Unfaired Cable, Ellsworth, W., Pneumodynamics Corp., October, 1960, 59 pp.

A method for rapid selection of design parameters to satisfy requirements for cable-towed instrument system is described. Curves are presented which facilitate the determination of cable diameter, cable length, and required down force without the need for performing cable calculations.

31. Program for the Stability Analysis of a Towed Body, Schuman, E., Naval Ordnance Lab., 27 October 1964, 27 pp.

Two computer programs are discussed which analyze the stability of a body towed in air. A detailed description of input and output are included.

32. Stability of a Towed Object, Reid, W., Naval Ordnance Lab., October 1964, 24 pp.

Problem: That of a bilaterally symmetrical object being pulled along in air in a straight line at constant speed by a single towline, which is assumed to remain straight and of constant length. Linearized approximation to the diff. equations of motion are developed. Two characteristic

equations are obtained from these by postulating exponential solutions.

A criterion for stability is then that the roots of these equations have only negative real parts.

33. On the Action of Wind on Flexible Cables with Application to Cables Towed Below Airplanes and Balloon Cables, McLeod, ARC, R & M 554, 1918.
34. Tables for Computing the Equilibrium Configuration of a Flexible Cable in a Uniform Stream, TMB Report 687, March, 1951.
35. Preliminary Theoretical Investigation of Several Methods for Stabilizing the Lateral Motion of a High-Speed Fighter Airplane NACA, RM L52L24, March, 1953.
36. Characteristics of Long Towlines in Non-Maneuvering and Orbiting Flight, Woodward, W. C., NADC Report No. ED-6340, June 1963.
37. Longitudinal Equations of Motion of an Airborne Towed Vehicle Incorporating an Approximation of Cable Drag and Inertia Effects, Law, E., Princeton University, May 1964, 76 pp.

Longitudinal equations of motion of a cable and towed vehicle system are developed. Approximation for the effects of cable drag and inertia are included in the development. Cable is assumed to act as a rigid body hinged at both the towing aircraft and towed vehicle. The system thus has two degrees of freedom. However, in order to present the equation in the "familiar language of aircraft dynamics," 5 equations in 5 unknowns are utilized.
38. On The Lateral Vibration of Rotating, Orbiting Cables, Targoff, W. P., AIAA 3rd Aerospace Sciences Meeting, 1966.
39. Mechanics of Flexible Lines, Langer, R. M., AIAA 3rd Aerospace Sciences Meeting, 1966.
40. A Note on the Drag Force on Wires, Morgan, P.G., Applied Scientific Research, Section A, Vol. 15, No. 4-5, 1966, pp. 394-396.